



Energy and structural Performance Tradition - Awning - Wood - Natural

INFORMATION

SDL : Simulated Divided Light is composed of small bars glued directly on both sides of the glass surface to simulate the appearance of true divided lites.

U Factor: (Btu/h-ft²-F) The lower the U-factor, the better the ability to resist to heat transfer.

SHGC: Solar Heat Gain Coefficient, the higher the SHGC, the more the solar heat is transmitted inside.

ER: The Energy Rating is the result of a formula taking into account the U-value, the SHGC and the airtightness of the product. The ER value measures the overall performance of a window. The higher the value, the better the product efficiency in terms of energy.

NFRC : National Fenestration Rating Council

VT Visible transmittance (expressed as a number from 0 to 1) also known as Visible light transmission (VLT - expressed as a percentage %) is a measurement of the amount of light in the visible portion of the spectrum that passes through glass

NFRC CODE	THERMOS	CODE	U Factor/ (Btu/h-ft ² -F)	Solar Heat Gain Coefficient (SHGC)	Visible transmittance (VT)	Energy Rating (ER)
MPE-M-2-00013	SG-400 double	3mm_7/8_PCl-arg95-SG400#3, su	0.29	0.48	0.53	31
MPE-M-2-00014	SG-400 double	3mm_7/8_PCl-arg95-SG400#3, su, Grids<1"	0.29	0.44	0.48	29
MPE-M-2-00015	SG-400 double	3mm_7/8_PCl-arg95-SG400#3, su, SDL<1"	0.29	0.44	0.48	29
MPE-M-2-00016	SG-400 double	3mm_7/8_PCl-arg95-SG400#3, su, SDL>1"	0.29	0.40	0.43	27
MPE-M-2-00017	SG-400 double	3mm_7/8_PCl-arg95-SG400#3, su, SDL-SB<1"	0.29	0.44	0.48	29
MPE-M-2-00018	SG-400 double	3mm_7/8_PCl-arg95-SG400#3, su, SDL-SB>1"	0.29	0.40	0.43	27
MPE-M-2-00019	SB-60 double	3mm_7/8_PCl-arg95-SB60#3, su	0.27	0.33	0.49	25
MPE-M-2-00020	SB-60 double	3mm_7/8_PCl-arg95-SB60#3, su, Grids<1"	0.27	0.31	0.44	24
MPE-M-2-00021	SB-60 double	3mm_7/8_PCl-arg95-SB60#3, su, SDL<1"	0.27	0.31	0.44	24
MPE-M-2-00022	SB-60 double	3mm_7/8_PCl-arg95-SB60#3, su, SDL>1"	0.27	0.28	0.39	22
MPE-M-2-00023	SB-60 double	3mm_7/8_PCl-arg95-SB60#3, su, SDL-SB<1"	0.27	0.31	0.44	24
MPE-M-2-00024	SB-60 double	3mm_7/8_PCl-arg95-SB60#3, su, SDL-SB>1"	0.27	0.28	0.39	22

Structural Performance

PERFORMANCE TESTING IN ACCORDANCE WITH AAMA/WDMA/CSA 101/I.S.2/A440-08

Performance Grade (PG)	Airtightness	Water tightness	Wind load resistance	Screen resistance	Resistance to forced entry	Usability	Structural test
LC-CP80-AP	A3	B7	C5	S1	F20	Successful	PES 80

PG: Performance Grade from the NAFS-08 harmonized standard (North American Fenestration Standard) for a given size on a scale from PG15 to PG100. The higher the value is, the better the product efficiency.

Airtightness: Resistance to air exfiltration/infiltration on a scale ranging from A1 to A3. The higher the value, the greater the sealing.

Water tightness: Resistance to water infiltration on a scale ranging from B1 to B7. The higher the value, the greater the sealing.

Wind load resistance: Resistance to wind pressures on a scale ranging from C1 to C5 without breakage or permanent deformation. The higher the value, the greater the resistance.

Screen resistance: Resistance rating without damage or permanent deformation while remaining firmly attached to the window under a force of 60 Newtons outwards.

Resistance to forced entry: Capacity when locked to withstand a forced entry under specified load and conditions for a rating of F10 or F20. The higher the value, the greater the resistance.

Usability: Test for measuring the force required to initiate and maintain the opening movement of the window or the door.

Structural test: Structural test pressure (STP) [greater than values specified in pounds per square foot (psf) or in pascals (Pa)] supported before permanent deformation measured on the jamb of the sash. Maximum values indicated.